




	PRODUCT CHARACTERISTICS			
	Standard	Requirement	Unit	Results
<b>PRODUCT DESCRIPTION</b>				
Surface treatment	-	-	-	<b>Protectorsol</b> <small>TRIPLE ACTION</small>
Surface complex	-	-	-	100% pur PVC
Foam	-	-	-	<b>COMFORT CXP</b>
Thickness	EN 428	-	mm	3.9
Weight	EN 430	-	kg/m <sup>2</sup>	1.95
Length	EN 426	-	lm	16 Standard
Width	EN 426	-	lm	1.5
<b>SPORT PROPERTIES</b>				
Shock absorption	EN 14808	≥ 25	%	-
Vertical deformation	EN 14809	≤ 3.5	mm	-
Energy return	NF P 90 203	≥ 0.31	m/s	-
Sliding coefficient	EN 13036-4	80 to 110	-	80 - 110
Ball bounce	EN 12235	≥ 90	%	-
Ball speed	UEFA	50 to 65	cm	-
	ITF	-	-	-
<b>TECHNICAL CHARACTERISTICS</b>				
Abrasion resistance	EN ISO 5470-1	≤ 1000	mg	≤ 350
Impact resistance	EN 1517	≥ 8	N/m	-
Indentation resistance	EN 1516	≤ 0.5	mm	≤ 0.5
<b>CLASSIFICATION</b>				
Fire	EN 13501-1	-	-	 Br-s1
Special treatment	-	-	-	<b>Sanosol</b> <small>SYSTEME</small>
Anti-bacterial activity (E. coli - S. aureus - MRSA) (3)	ISO 22196	-	-	> 99.9 % inhibits growth
<b>DECLARATION OF PERFORMANCE</b>				
	DOP-005-1020-A	-	-	Fire

	INSTALLATION METHODS		
	Gerflor's recommendation	Unit	Results
Loose lay installation with double sided adhesive tapes	-	-	-

COLOUR RANGE	
	6570 Mint Green Canvas embossing

(3) The implementation of an effective cleaning method is the best defence against infection



Health & Safety Life Cycle Analysis

ISO 14001

Recycling

TVOC  
< 100  
µg m<sup>3</sup>  
over 24h