

Level of use EN 1470	class 33 heavy duty						
Emission tested acc. to DIBt principles acc. to CRI principles	abZ-Nr.: Z-156.601-736 Green Label Plus 2654						
Health safety Environmental label RAL-UZ 128	Blue Angel Contract No.: 21030						
Wear layer	30% polyamide dorix / 70% polypropylene						
Back	Polyolefin heavy-weight backing						
Total thickness ISO 1765	4,8 mm						
Total weight ISO 8543	3000 g/m ²						
Fibre weight	700 g/m ²						
Dimensions	Tile 50 x 50 cm, VE 4m ² /carton						
Fire rating EN 13501-1	Bfl-s1						
Sound absorption ISO 10140	21 dB *						
Level of sound absorption ISO 354	Freq. Hz	125	250	500	1000	2000	4000 *
	α _s	0,02	0,03	0,13	0,33	0,23	0,27
	α _w	0,25 *					
Colour fastness to light ISO 105-B02	7						
Thermal resistance ISO 8302	0,08 m ² K/W * suitable for underfloor heating						
Anti-Static ISO 6356	≤ 0,8 kV						
Special colours	> 1000 m ²						
Installation DIN 18365	Full-surface and releasable gluing with a suitable tackifier (adhesive). A recommendation of suitable adhesives is enclosed with every supply.						
	* proofed on gluesystem Teppichlifter „Soft“						

Subject to improvements and usual colour deviations. The explanations in our technical instruction card as well as our cleaning and maintenance instructions have to be observed. Additional technical details upon request.



heavy duty



FINDEISEN GmbH

Bulacher Str. 53 | D-76275 Ettlingen | Telefon +49 7243 7100-0 | Telefax +49 7243 12760 | info@finett.de | www.findeisen-nadelvlies.de