

HARO

Sports

Datasheet Munich 50F

Type: Area elastic sports floor
 Use: sports and multipurpose use
 Underfloor heating compatible



1. HARO load distribution module
2. PE-Foil
3. HARO counter floor
4. HARO double swing beam

| | Installation from the top edge of raw concrete |
|---------|---|
| 54 mm | Module unit HARO double swing beam, with intermediate bars, damping elements and support beams, distance centre to centre: 444 mm, laid out in longitudinal direction of the hall |
| 15 mm | Counter floor module, distance centre/centre: 125mm fixed in transverse position on the HARO double swing beam module unit. The spruce modules are kiln-dried, parallel edged, planed on all sides, manufactured in fixed lengths |
| 0.03 mm | PE-foil, 10% overlapped, loosely laid out |
| 12 mm | HARO load distribution module screwed onto the counter floor modules, made of special plywood plates, BFU 100 according to DIN 68705, part 3 |
| 81 mm | Construction height (without sports coating) |

Model Munich 50F meets and exceeds DIN V 18032-2; April 2001, EN 14904 and is subject to RAL- GZ 942 quality assurance. This floor has a general building authority approval in connection with certain surfaces.



Hamberger Flooring GmbH & Co. KG
 Rohrdorfer Straße 133, 83071 Stephanskirchen, DE
 Phone +49 8031 700-240, Fax +49 8031 700-249
 email info@haro-sports.com, web www.haro-sports.com