


# BLOQ

creative  
carpet tiles






## THE BINARY FLOW

### SPECIFICATIONS

|                               |                                                                |
|-------------------------------|----------------------------------------------------------------|
| <b>TYPE OF MANUFACTURE</b>    | Tufted Patterned Loop Pile 1/10"                               |
| ISO 2424                      |                                                                |
| <b>PILE FIBER COMPOSITION</b> | 100% Polyamide 6                                               |
| ISO 2424                      | Solution Dyed Nylon made by Aquafil                            |
| <b>SECONDARY BACKING</b>      | Bitback, Modified Bitumen                                      |
| ISO 2424                      | 70% Recycled Content                                           |
| <b>DIMENSION</b>              | 50 x 50 cm                                                     |
| EN ISO 24342                  |                                                                |
| <b>PILE WEIGHT</b>            | 650 g/m <sup>2</sup>                                           |
| ISO 8543                      |                                                                |
| <b>SURFACE PILE WEIGHT</b>    | 380 g/m <sup>2</sup>                                           |
| ISO 8543                      |                                                                |
| <b>TOTAL WEIGHT</b>           | 4 400 g/m <sup>2</sup>                                         |
| ISO 8543                      |                                                                |
| <b>TOTAL THICKNESS</b>        | 6.9 mm                                                         |
| ISO 1765                      |                                                                |
| <b>PILE HEIGHT</b>            | 3.8 mm                                                         |
| ISO 1766                      |                                                                |
| <b>PILE DENSITY</b>           | 0.100 g/m <sup>3</sup>                                         |
| ISO 8543                      |                                                                |
| <b>NUMBER OF TUFTS</b>        | 152 000 /m <sup>2</sup>                                        |
| ISO 1763                      |                                                                |
| <b>DIMENSIONAL STABILITY</b>  | ≤ 0.2%                                                         |
| ISO 2551                      |                                                                |
| <b>NUMBER OF COLOURS</b>      | 18                                                             |
| <b>PACKAGING</b>              | Box: 20 tiles / 5 m <sup>2</sup><br>Pallet: 200 m <sup>2</sup> |

### PERFORMANCE

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| <b>CLASSIFICATION</b>           | 33                                           |
| EN 1307                         |                                              |
| <b>LUXURY RATING</b>            | LC1                                          |
| EN 1307                         |                                              |
| <b>CASTOR CHAIR RATING</b>      | A: Intensive use                             |
| EN 985                          |                                              |
| <b>FIRE CLASSIFICATION</b>      | B <sub>fl</sub> -s1                          |
| EN 13501-1                      |                                              |
| <b>IMPACT SOUND INSULATION</b>  | ΔL <sub>w</sub> : 26 dB                      |
| EN ISO 10140-3                  |                                              |
| <b>SOUND ABSORPTION</b>         | Frequency Hz 125 250 500 1000 2000 4000      |
| EN ISO 354                      | α <sub>s</sub> 0.01 0.03 0.08 0.22 0.32 0.39 |
| <b>NOISE REDUCTION</b>          | α <sub>w</sub> : 0.20                        |
| EN ISO 354                      |                                              |
| <b>PERMANENT ANTISTATIC</b>     | ≤ 2 kV                                       |
| ISO 6356                        |                                              |
| <b>TRANSVERSAL RESISTANCE</b>   | ≤ 1 X 10 <sup>9</sup> Ohm                    |
| ISO 10965                       |                                              |
| <b>THERMAL RESISTANCE</b>       | 0.080 m <sup>2</sup> K/W                     |
| ISO 8302                        |                                              |
| <b>COLOUR FASTNESS TO LIGHT</b> | ≥ 7                                          |
| EN ISO 105-B02                  |                                              |
| <b>COLOUR FASTNESS TO WATER</b> | ≥ 4                                          |
| EN ISO 105-E01                  |                                              |
| <b>RUBBING FASTNESS</b>         | ≥ 4                                          |
| EN ISO 105-X12                  |                                              |
| <b>GUT N° PRODIS</b>            | 63C72CE9                                     |



13/02/2024

All rights reserved to alter technical specifications.